

REMEDIA SMOKE OUT

SMOKE, SOOT, CARBON AND GREASE REMOVER



Remedia **SMOKE OUT** is a combination of special solvents, detergents, and penetrating surfaces that are designed to penetrate through smoke, soot, carbon and grease to lift the soils off of surfaces and hold them in solution until they can be removed by wiping or rinsing. Because of the penetrating qualities and lifting abilities of Remedia **SMOKE OUT**, the soot and smoke are removed from the pores below the surface and brought to the top for easy removal, thus aiding in the elimination of smoke odor. Remedia **SMOKE OUT** can be used on any water-safe surface. This includes metal, wood or any other water-safe porous or nonporous surface. Remedia **SMOKE OUT** is nonflammable and will not support combustion.

DIRECTIONS:

Light to Mild Soils:

Dilute Remedia **SMOKE OUT** from 1 part up to 1 part **SMOKE OUT** to 1 part to 5 parts of water. The finished solution can be sprayed or wiped on the surface. Allow surface to stay wet for 5 to 10 minutes, and then remove by rinsing or wiping.

Heavy Soils:

Apply **SMOKE OUT** undiluted by spraying or wiping. Allow to stand 5 to 10 minutes, and then rinse or wipe clean. For best results, where applicable apply and rinse with a pressure washer.

It is recommended to allow the surface to dry to below 15% and then to apply Remedia 1 which will remove any remaining smoke, soot, carbon, or grease residue and eliminate all odors.

Revised 03202012



HILL MANUFACTURING COMPANY, INC.

1500 JONESBORO RD, SE ATLANTA, GA 30315

404-522-8364 1-800-445-5123 www.hillmfg.com

PROVEN SOLUTIONS TO MAINTENANCE PROBLEMS